



AC-HW

cable clamp for fastening to C-profile rails

HF cable clamp with all-over vat made of galvanised steel and plastic half-vats made of polystyrene. For fastening to C-profile rails (C+, C60°) with a slot size of 18/22 mm.

Zinc coated

| Product | B | D | H _{max} | number of cables | G |
|------------|-------|------------|------------------|------------------|--------------|
| 20 AC-HW | 20 mm | 1/2 inch | 53 mm | 1 | 4,42 kg/100 |
| 32 AC-HW | 32 mm | 7/8 inch | 68 mm | 1 | 8,6 kg/100 |
| 44 AC-HW | 44 mm | 1 1/4 inch | 83 mm | 1 | 10,2 kg/100 |
| 56 AC-HW | 56 mm | 1 5/8 inch | 106 mm | 1 | 16,82 kg/100 |
| 20/2 AC-HW | 20 mm | 1/2 inch | 73 mm | 2 | 6,44 kg/100 |
| 32/2 AC-HW | 32 mm | 7/8 inch | 102 mm | 2 | 13,3 kg/100 |
| 44/2 AC-HW | 44 mm | 1 1/4 inch | 129 mm | 2 | 20,5 kg/100 |
| 56/2 AC-HW | 56 mm | 1 5/8 inch | 164 mm | 2 | 26,54 kg/100 |
| 20/3 AC-HW | 20 mm | 1/2 inch | 93 mm | 3 | 8,66 kg/100 |
| 32/3 AC-HW | 32 mm | 7/8 inch | 136 mm | 3 | 18 kg/100 |
| 44/3 AC-HW | 44 mm | 1 1/4 inch | 176 mm | 3 | 28,6 kg/100 |

Stainless steel, according to ASTM 304 / BS 304 S 3

| Product | B | D | H _{max} | number of cables | G |
|--------------|-------|------------|------------------|------------------|-------------|
| 20 AC-HW-E | 20 mm | 1/2 inch | 53 mm | 1 | 4,12 kg/100 |
| 32 AC-HW-E | 32 mm | 7/8 inch | 68 mm | 1 | 7 kg/100 |
| 44 AC-HW-E | 44 mm | 1 1/4 inch | 83 mm | 1 | 12,3 kg/100 |
| 56 AC-HW-E | 56 mm | 1 5/8 inch | 106 mm | 1 | 16,1 kg/100 |
| 20/2 AC-HW-E | 20 mm | 1/2 inch | 73 mm | 2 | 6,14 kg/100 |



| Product | B | D | H _{max} | number of cables | G |
|--------------|-------|------------|------------------|------------------|-------------|
| 32/2 AC-HW-E | 32 mm | 7/8 inch | 102 mm | 2 | 11,7 kg/100 |
| 44/2 AC-HW-E | 44 mm | 1 1/4 inch | 129 mm | 2 | 19,1 kg/100 |
| 32/3 AC-HW-E | 32 mm | 7/8 inch | 136 mm | 3 | 15,9 kg/100 |
| 44/3 AC-HW-E | 44 mm | 1 1/4 inch | 176 mm | 3 | 26 kg/100 |

B: width

D: diameter

H_{max}: Maximum height

number of cables: Maximum number of installable cables

G: weight

DETAILS / APPLICATIONS

