

AMK 22

Channel nut with plastic bracket

Channel nuts with plastic fixing aid AMK 22 are threaded plates that are used with mounting rails A 41, KHA 41 and KHAL 41. A 90° turn after insertion or tilting holds the nut in the mounting/profile rail. The plastic fixing aid is used to hold the anchor nut in position. The anchor nuts, also known as rail nuts, can be positioned precisely after installation thanks to the pronounced toothing. Ideally suited for vertically installed rails. Another advantage is that no spring is used, which can jam in perforated rails. AMK 22 are available in M6, M8, M10 and M12 threads. Different materials and surfaces ensure that the corrosion protection requirements of a wide range of applications are met.

Hot-dip galvanized, according to BS 729 (DIN EN ISO 1461)

Product	t	Ø	G
AMK222 M6F	6,00 mm	6,0 mm	0,029 kg
AMK22 M8F	6,00 mm	6,0 mm	0,028 kg
AMK22 M10F	8,00 mm	10,00 mm	0,034 kg
AMK22 M12F	9,00 mm	12,00 mm	0,036 kg

galvanized, according to ISO 19598 / ISO 2081

Product	t	Ø	G
AMK22 M6	6,00 mm	6,0 mm	0,028 kg
AMK22 M8	6,00 mm	8,0 mm	0,027 kg
AMK22 M10	6,00 mm	10,0 mm	0, 034 kg
AMK22 M12	9,00 mm	12,0 mm	0,036 kg

t: material thickness
Ø: diameter
G: weight

PohlCon Benelux Cable Support B.V.
Meerheide 212, 5521 DW Eersel | The Netherlands
Telefoon: +31 497 799 700 | Fax: +31 497 799 735 | info@pohlconbenelux.com | pohlconbenelux.com

Date of issuance: 08.11.2026. Errors and technical modifications reserved.

OPTIONAL ACCESSORIES

A 41, KHA 41, KHAL 41

PohlCon Benelux Cable Support B.V.
Meerheide 212, 5521 DW Eersel | The Netherlands
Telefoon: +31 497 799 700 | Fax: +31 497 799 735 | info@pohlconbenelux.com | pohlconbenelux.com

Date of issuance: 08.11.2026. Errors and technical modifications reserved.