



## FRSV

round-head screw with short square, DIN 603

### galvanized, according to DIN EN ISO 19598 / DIN EN ISO 2081

Product	L	D	Ø	d	G
FRSV 6X12	12 mm	16 mm	6 mm	1,5 mm	0,5 kg/100
FRSV 8X16	16 mm	20 mm	8 mm	2 mm	1,3 kg/100
FRSV 10X20	20 mm	24 mm	10 mm	2,5 mm	2,3 kg/100

### Hot-dip galvanized, according to BS 729 (DIN EN ISO 1461)

Product	L	D	Ø	d	G
FRSV 10X20F	20 mm	24 mm	10 mm	2,5 mm	2,3 kg/100

### Stainless steel, according to ASTM 304 / BS 304 S 3

Product	L	D	Ø	d	G
FRSV 6X12E	12 mm	16 mm	6 mm	1,5 mm	0,5 kg/100
FRSV 8X16E	16 mm	20 mm	8 mm	2 mm	1,3 kg/100
FRSV 10X20E	20 mm	24 mm	10 mm	2,5 mm	2,3 kg/100

### Stainless steel, according to ASTM 31 Ti / AISI 316 L, BS 320S17 / BS 316S11





Product	L	D	Ø	d	G
FRSV 6X12E4	12 mm	16 mm	6 mm	1,5 mm	0,5 kg/100
FRSV 10X20E4	20 mm	24 mm	10 mm	2,5 mm	2,4 kg/100

### Hot-dip galvanized, according to BS 729 (DIN EN ISO 1461)

Product	L	D	Ø	d	G
FRSV 10X20-HDG	20 mm	24 mm	10 mm	2,5 mm	2,20 kg/100

### Stainless steel, according to ASTM 304 / BS 304 S 3

Product	L	D	Ø	d	G
FRSV 6X12-304	12 mm	16 mm	6 mm	1,5 mm	0,50 kg/100
FRSV 6X16-304	16 mm	16 mm	6 mm	1,5 mm	0,7 kg/100
FRSV 8X16-304	16 mm	20 mm	8 mm	2 mm	1,3 kg/100
FRSV 10X20-304	20 mm	24 mm	10 mm	2,5 mm	2,20 kg/100

### Stainless steel, according to ASTM 31 Ti / AISI 316 L, BS 320S17 / BS 316S11

Product	L	D	Ø	d	G
FRSV 6X12-316	12 mm	16 mm	6 mm	1,5 mm	0,50 kg/100
FRSV 10X20-316	20 mm	24 mm	10 mm	2,5 mm	2,40 kg/100

**L:** length  
**D:** diameter  
**Ø:** diameter  
**d:** thickness  
**G:** weight

## DETAILS / APPLICATIONS



