


LGK 100

cable ladder crossing, height = 100 mm

cable ladder crossing for horizontal change of direction



Hot-dip galvanized, according to BS 729 (DIN EN ISO 1461)

Product	H	B	R	G
LGK 100-20F	100 mm	200 mm	400 mm	9,32 kg
LGK 100-30F	100 mm	300 mm	400 mm	10,13 kg
LGK 100-40F	100 mm	400 mm	400 mm	10,94 kg
LGK 100-50F	100 mm	500 mm	400 mm	11,74 kg
LGK 100-60F	100 mm	600 mm	400 mm	12,55 kg


Stainless steel, according to ASTM 304 / BS 304 S 3

Product	H	B	R	G
LGK 100-20E	100 mm	200 mm	400 mm	8,77 kg
LGK 100-30E	100 mm	300 mm	400 mm	9,53 kg
LGK 100-40E	100 mm	400 mm	400 mm	10,29 kg
LGK 100-50E	100 mm	500 mm	400 mm	11,05 kg
LGK 100-60E	100 mm	600 mm	400 mm	11,81 kg

H: height
B: width
R: radius
G: weight



DETAILS / APPLICATIONS



OPTIONAL ACCESSORIES

LGV 100, LGVH 100, LGVV 100, KLU, LKD, LKDR, LGTRV 100



UL classified

