

MP-G90

assembly plate 90°

assembly plate for fixing of distribution boxes



Continuously hot galvanized (Sendzimir process) (DIN EN 10346)

| Product | H | B | G |
|--------------|---|--------|---------|
| MP-G90 50S | 198 mm | 120 mm | 0,16 kg |
| incl.: | | | |
| 1x SEMS 8 | hexagon-nut with flange, DIN EN 1661 | | |
| 1x FRSV 8X16 | round-head screw with short square, DIN 603 | | |
| 1x GV-L 30F | mesh cable tray connector | | |

Hot-dip galvanized, according to BS 729 (DIN EN ISO 1461)

| Product | H | B | G |
|---------------|---|--------|---------|
| MP-G90 50F | 198 mm | 120 mm | 0,17 kg |
| incl.: | | | |
| 1x SEMS 8E | hexagon-nut with flange, DIN EN 1661 | | |
| 1x FRSV 8X16E | round-head screw with short square, DIN 603 | | |
| 1x GV-L 30F | mesh cable tray connector | | |

Stainless steel, according to ASTM 31 Ti / AISI 316 L, BS 320S17 / BS 316S11

| Product | H | B | G |
|-------------|--------|--------|---------|
| MP-G90 50E4 | 198 mm | 120 mm | 0,16 kg |



| Product | H | B | G |
|---|---|---|---|
| incl.: 1x SEM 8E4 1x SES 8X20E4 1x GV-L 30E4 | | | |
| | | hexagon-nut, DIN 934 hexagon head bolt, DIN 933 mesh cable tray connector | |

H: height
B: width
G: weight

DETAILS / APPLICATIONS

