



## RU

cable clamp for fastening to round and flat profiles

Cable clamp with all-over vat made of galvanised steel, for fastening to round and flat profiles up to 22 mm.

Hot-dip galvanized, according to BS 729 (DIN EN ISO 1461)

| Product     | D        | H <sub>max</sub> | M    | number of cables | G            |
|-------------|----------|------------------|------|------------------|--------------|
| 14 RU-HDG   | 8-14 mm  | 48 mm            | 2 Nm | 1                | 4,30 kg/100  |
| 20 RU-HDG   | 14-20 mm | 54 mm            | 2 Nm | 1                | 4,90 kg/100  |
| 26 RU-HDG   | 20-26 mm | 60 mm            | 2 Nm | 1                | 5,90 kg/100  |
| 32 RU-HDG   | 26-32 mm | 67 mm            | 2 Nm | 1                | 9,20 kg/100  |
| 38 RU-HDG   | 32-38 mm | 74 mm            | 2 Nm | 1                | 10,50 kg/100 |
| 44 RU-HDG   | 38-44 mm | 82 mm            | 4 Nm | 1                | 12,00 kg/100 |
| 52 RU-HDG   | 44-52 mm | 91 mm            | 4 Nm | 1                | 14,30 kg/100 |
| 60 RU-HDG   | 52-60 mm | 99 mm            | 4 Nm | 1                | 16,40 kg/100 |
| 70 RU-HDG   | 60-70 mm | 109 mm           | 4 Nm | 1                | 18,40 kg/100 |
| 14/2 RU-HDG | 8-14 mm  | 63 mm            | 2 Nm | 2                | 5,6 kg/100   |
| 20/2 RU-HDG | 14-20 mm | 75 mm            | 2 Nm | 2                | 6,80 kg/100  |
| 26/2 RU-HDG | 20-26 mm | 88 mm            | 2 Nm | 2                | 6,80 kg/100  |
| 32/2 RU-HDG | 26-32 mm | 101 mm           | 2 Nm | 2                | 12,50 kg/100 |

**D:** diameter

**H<sub>max</sub>:** Maximum height

**M:** torque

**number of cables:** Maximum number of installable cables

**G:** weight



## DETAILS / APPLICATIONS

