



## S-IW

cable clamp with additional insulating vat for fastening to angle profiles

Cable clamp with full-surface vat made of galvanised steel and additional insulating vat made of polystyrene. For fastening to angle profiles with a side length of up to max. 43 mm.

**Zinc coated**

Product	D	H <sub>max</sub>	M	number of cables	G
12 S-IW	8-12 mm	42,5 mm	2 Nm	1	3,8 kg/100
16 S-IW	12-16 mm	47,5 mm	2 Nm	1	4,3 kg/100
20 S-IW	16-20 mm	51,5 mm	2 Nm	1	4,8 kg/100
24 S-IW	20-24 mm	55,7 mm	2 Nm	1	5,1 kg/100
28 S-IW	24-28 mm	59,7 mm	2 Nm	1	5,5 kg/100
32 S-IW	28-32 mm	65 mm	2 Nm	1	8,3 kg/100
36 S-IW	32-36 mm	69 mm	2 Nm	1	8,9 kg/100
40 S-IW	36-40 mm	73 mm	2 Nm	1	9,3 kg/100
44 S-IW	40-44 mm	83 mm	4 Nm	1	11,8 kg/100
48 S-IW	44-48 mm	87 mm	4 Nm	1	12,4 kg/100
52 S-IW	48-52 mm	92,5 mm	4 Nm	1	13,3 kg/100
56 S-IW	52-56 mm	96,5 mm	4 Nm	1	14 kg/100
60 S-IW	56-60 mm	100,5 mm	4 Nm	1	18,4 kg/100
64 S-IW	60-64 mm	104,5 mm	4 Nm	1	19,1 kg/100
70 S-IW	64-70 mm	111,5 mm	4 Nm	1	20,2 kg/100

**D:** diameter

**H<sub>max</sub>:** Maximum height

**M:** torque

**number of cables:** Maximum number of installable cables

**G:** weight



## DETAILS / APPLICATIONS

