



## WPC 100

wide-span connector, height = 100 mm

In order to compensate for the heat expansion one side of the connector is mounted as a loose bearing. The given torques must be observed. The other side of the connector is to be mounted as a fixed bearing. A minimum distance of 4mm must be kept between the cable ladders. Electrical conductivity tested according to DIN EN 61537.



### Hot-dip galvanized, according to BS 729 (DIN EN ISO 1461)

Product	H	L	G
WPC10-HDG	100 mm	400 mm	1,03 kg
incl.:			
4x KLS 10X20-HDG		clamp fastening set	
4x FRSV 10X20-HDG		round-head screw with short square, DIN 603	
4x SEMB 10-HDG		hexagon-nut, DIN 934	

### Stainless steel, according to ASTM 304 / BS 304 S 3

Product	H	L	G
WPC10-304	100 mm	400 mm	0,98 kg
incl.:			
4x KLS 10X20-304		clamp fastening set	
4x FRSV 10X20-304		round-head screw with short square, DIN 603	
4x SEMSS 10-304		hexagon-nut, self-locking, DIN 985	

### Stainless steel, according to ASTM 31 Ti / AISI 316 L, BS 320S17 / BS 316S11

Product	H	L	G
WPC10-316	100 mm	400 mm	0,99 kg



Product	H	L	G
incl.: 4x KLS 10X20-316 4x FRSV 10X20-316 4x SEMSS 10-316			clamp fastening set round-head screw with short square, DIN 603 hexagon-nut, self-locking, DIN 985

**H:** height  
**L:** length  
**G:** weight

## DETAILS / APPLICATIONS

