



## WPIR 60

wide-span inside riser, height = 60 mm

wide-span cable ladder bend 90° for vertical change of direction with integrated connectors

Welded construction. Formed components must be supported at all sides.

Hot-dip galvanized, according to BS 729 (DIN EN ISO 1461)

Product	H	B	angle	R	G
WPIR06-15-90-30-HDG	60 mm	150 mm	90 °	300 mm	3,26 kg
incl.:					
8x KLS 10X20-HDG					clamp fastening set
WPIR06-20-90-30-HDG	60 mm	200 mm	90 °	300 mm	3,51 kg
incl.:					
8x KLS 10X20-HDG					clamp fastening set
WPIR06-30-90-30-HDG	60 mm	300 mm	90 °	300 mm	3,87 kg
incl.:					
8x KLS 10X20-HDG					clamp fastening set
WPIR06-40-90-30-HDG	60 mm	400 mm	90 °	300 mm	4,23 kg
incl.:					
8x KLS 10X20-HDG					clamp fastening set
WPIR06-60-90-30-HDG	60 mm	600 mm	90 °	300 mm	4,95 kg
incl.:					
8x KLS 10X20-HDG					clamp fastening set

**H:** height  
**B:** width  
**angle:** angle  
**R:** radius  
**G:** weight



## DETAILS / APPLICATIONS

