



WPIRCO

wide-span inside riser cover

If the cover is to be mounted elevated, this must be mentioned separately in your order, e.g. WPIRCOE In our additional information is explained which amount of fitting cover hook clips you need. The following angles are available on request: 30 °, 45 °, 60 °. The following radii are available on request: 300 mm, 600 mm, 900 mm.

Hot-dip galvanized, according to BS 729 (DIN EN ISO 1461)

Product	B	angle	R	G
WPIRCO20-90-45-HDG	200 mm	90 °	450 mm	2,04 kg
WPIRCO30-90-45-HDG	300 mm	90 °	450 mm	3,75 kg
WPIRCO40-90-45-HDG	400 mm	90 °	450 mm	4,79 kg
WPIRCO45-90-45-HDG	450 mm	90 °	450 mm	6,64 kg
WPIRCO50-90-45-HDG	500 mm	90 °	450 mm	7,29 kg
WPIRCO60-90-45-HDG	600 mm	90 °	450 mm	8,59 kg
WPIRCO70-90-45-HDG	700 mm	90 °	450 mm	11,87 kg
WPIRCO75-90-45-HDG	750 mm	90 °	450 mm	12,64 kg
WPIRCO80-90-45-HDG	800 mm	90 °	450 mm	13,42 kg
WPIRCO90-90-45-HDG	900 mm	90 °	450 mm	14,98 kg
WPIRCO100-90-45-HDG	1000 mm	90 °	450 mm	15,30 kg

Stainless steel, according to ASTM 304 / BS 304 S 3

Product	B	angle	R	G
WPIRCO20-90-45-304	200 mm	90 °	450 mm	1,91 kg
WPIRCO30-90-45-304	300 mm	90 °	450 mm	3,50 kg
WPIRCO40-90-45-304	400 mm	90 °	450 mm	4,48 kg
WPIRCO45-90-45-304	450 mm	90 °	450 mm	6,64 kg
WPIRCO50-90-45-304	500 mm	90 °	450 mm	6,81 kg





Product	B	angle	R	G
WPIRCO60-90-45-304	600 mm	90 °	450 mm	8,03 kg
WPIRCO70-90-45-304	700 mm	90 °	450 mm	11,87 kg
WPIRCO75-90-45-304	750 mm	90 °	450 mm	12,64 kg
WPIRCO80-90-45-304	800 mm	90 °	450 mm	13,42 kg
WPIRCO90-90-45-304	900 mm	90 °	450 mm	14,98 kg
WPIRCO100-90-45-304	1000 mm	90 °	450 mm	15,30 kg

Stainless steel, according to ASTM 31 Ti / AISI 316 L, BS 320S17 / BS 316S11

Product	B	angle	R	G
WPIRCO20-90-45-316	200 mm	90 °	450 mm	2,03 kg
WPIRCO30-90-45-316	300 mm	90 °	450 mm	3,50 kg
WPIRCO40-90-45-316	400 mm	90 °	450 mm	4,52 kg
WPIRCO45-90-45-316	450 mm	90 °	450 mm	6,64 kg
WPIRCO50-90-45-316	500 mm	90 °	450 mm	6,81 kg
WPIRCO60-90-45-316	600 mm	90 °	450 mm	8,03 kg
WPIRCO70-90-45-316	700 mm	90 °	450 mm	11,87 kg
WPIRCO75-90-45-316	750 mm	90 °	450 mm	12,64 kg
WPIRCO80-90-45-316	800 mm	90 °	450 mm	13,42 kg
WPIRCO90-90-45-316	900 mm	90 °	450 mm	14,98 kg
WPIRCO100-90-45-316	1000 mm	90 °	450 mm	15,30 kg

B: width
angle: angle
R: radius
G: weight

OPTIONAL ACCESSORIES

WPFCOH

