



WPOR 150

wide-span outside riser, height = 150 mm

wide-span cable ladder outside raiser 90° for vertical change of direction with integrated connectors

Welded construction. Formed components must be supported at all sides. The following angles are available on request: 30 °, 45 °, 60 °. The following radii are available on request: 300 mm, 600 mm, 900 mm.

Hot-dip galvanized, according to BS 729 (DIN EN ISO 1461)

Product	H	B	angle	R	G
WPOR15-20-90-45-HDG	150 mm	200 mm	90 °	450 mm	10,81 kg
incl.: 8x KLS 10X20-HDG					clamp fastening set
WPOR15-30-90-45-HDG	150 mm	300 mm	90 °	450 mm	11,44 kg
incl.: 8x KLS 10X20-HDG					clamp fastening set
WPOR15-40-90-45-HDG	150 mm	400 mm	90 °	450 mm	12,08 kg
incl.: 8x KLS 10X20-HDG					clamp fastening set
WPOR15-45-90-45-HDG	150 mm	450 mm	90 °	450 mm	12,40 kg
incl.: 8x KLS 10X20-HDG					clamp fastening set
WPOR15-50-90-45-HDG	150 mm	500 mm	90 °	450 mm	12,72 kg
incl.: 8x KLS 10X20-HDG					clamp fastening set
WPOR15-60-90-45-HDG	150 mm	600 mm	90 °	450 mm	13,35 kg
incl.: 8x KLS 10X20-HDG					clamp fastening set
WPOR15-70-90-45-HDG	150 mm	700 mm	90 °	450 mm	13,99 kg
incl.: 8x KLS 10X20-HDG					clamp fastening set
WPOR15-75-90-45-HDG	150 mm	750 mm	90 °	450 mm	14,31 kg





Product	H	B	angle	R	G
incl.: 8x KLS 10X20-HDG clamp fastening set					
WPOR15-80-90-45-HDG	150 mm	800 mm	90 °	450 mm	14,62 kg
incl.: 8x KLS 10X20-HDG clamp fastening set					
WPOR15-90-90-45-HDG	150 mm	900 mm	90 °	450 mm	15,26 kg
incl.: 8x KLS 10X20-HDG clamp fastening set					
WPOR15-100-90-45-HDG	150 mm	1000 mm	90 °	450 mm	15,90 kg
incl.: 8x KLS 10X20-HDG clamp fastening set					

Stainless steel, according to ASTM 304 / BS 304 S 3

Product	H	B	angle	R	G
WPOR15-20-90-45-304	150 mm	200 mm	90 °	450 mm	10,81 kg
incl.: 8x KLS 10X20-304 clamp fastening set					
WPOR15-30-90-45-304	150 mm	300 mm	90 °	450 mm	11,44 kg
incl.: 8x KLS 10X20-304 clamp fastening set					
WPOR15-40-90-45-304	150 mm	400 mm	90 °	450 mm	12,08 kg
incl.: 8x KLS 10X20-304 clamp fastening set					
WPOR15-45-90-45-304	150 mm	450 mm	90 °	450 mm	12,40 kg
incl.: 8x KLS 10X20-304 clamp fastening set					
WPOR15-50-90-45-304	150 mm	500 mm	90 °	450 mm	12,72 kg
incl.: 8x KLS 10X20-304 clamp fastening set					
WPOR15-60-90-45-304	150 mm	600 mm	90 °	450 mm	13,35 kg
incl.: 8x KLS 10X20-304 clamp fastening set					
WPOR15-70-90-45-304	150 mm	700 mm	90 °	450 mm	13,99 kg





Product	H	B	angle	R	G
incl.: 8x KLS 10X20-304					clamp fastening set
WPOR15-75-90-45-304	150 mm	750 mm	90 °	450 mm	14,31 kg
incl.: 8x KLS 10X20-304					clamp fastening set
WPOR15-80-90-45-304	150 mm	800 mm	90 °	450 mm	14,62 kg
incl.: 8x KLS 10X20-304					clamp fastening set
WPOR15-90-90-45-304	150 mm	900 mm	90 °	450 mm	15,26 kg
incl.: 8x KLS 10X20-304					clamp fastening set
WPOR15-100-90-45-304	150 mm	1000 mm	90 °	450 mm	15,90 kg
incl.: 8x KLS 10X20-304					clamp fastening set

Stainless steel, according to ASTM 31 Ti / AISI 316 L, BS 320S17 / BS 316S11

Product	H	B	angle	R	G
WPOR15-20-90-45-316	150 mm	200 mm	90 °	450 mm	10,81 kg
incl.: 8x KLS 10X20-316					clamp fastening set
WPOR15-30-90-45-316	150 mm	300 mm	90 °	450 mm	11,44 kg
incl.: 8x KLS 10X20-316					clamp fastening set
WPOR15-40-90-45-316	150 mm	400 mm	90 °	450 mm	12,08 kg
incl.: 8x KLS 10X20-316					clamp fastening set
WPOR15-45-90-45-316	150 mm	450 mm	90 °	450 mm	12,40 kg
incl.: 8x KLS 10X20-316					clamp fastening set
WPOR15-50-90-45-316	150 mm	500 mm	90 °	450 mm	12,72 kg
incl.: 8x KLS 10X20-316					clamp fastening set
WPOR15-60-90-45-316	150 mm	600 mm	90 °	450 mm	13,35 kg



Product	H	B	angle	R	G
incl.: 8x KLS 10X20-316					clamp fastening set
WPOR15-70-90-45-316	150 mm	700 mm	90 °	450 mm	13,99 kg
incl.: 8x KLS 10X20-316					clamp fastening set
WPOR15-75-90-45-316	150 mm	750 mm	90 °	450 mm	14,31 kg
incl.: 8x KLS 10X20-316					clamp fastening set
WPOR15-80-90-45-316	150 mm	800 mm	90 °	450 mm	14,62 kg
incl.: 8x KLS 10X20-316					clamp fastening set
WPOR15-90-90-45-316	150 mm	900 mm	90 °	450 mm	15,26 kg
incl.: 8x KLS 10X20-316					clamp fastening set
WPOR15-100-90-45-316	150 mm	1000 mm	90 °	450 mm	15,90 kg
incl.: 8x KLS 10X20-316					clamp fastening set

H: height
B: width
angle: angle
R: radius
G: weight

DETAILS / APPLICATIONS



