


WPR

reducer, height = 150 mm



Hot-dip galvanized, according to BS 729 (DIN EN ISO 1461)

Product	H	B	G
WPR15-10-HDG	150 mm	100 mm	1,71 kg
incl.: 4x KLS 10X20-HDG clamp fastening set			
WPR15-20-HDG	150 mm	200 mm	2,08 kg
incl.: 4x KLS 10X20-HDG clamp fastening set			
WPR15-30-HDG	150 mm	300 mm	2,44 kg
incl.: 4x KLS 10X20-HDG clamp fastening set			

Stainless steel, according to ASTM 304 / BS 304 S 3

Product	H	B	G
WPR15-10-304	150 mm	100 mm	1,62 kg
incl.: 4x KLS 10X20-304 clamp fastening set			
WPR15-20-304	150 mm	200 mm	1,96 kg
incl.: 4x KLS 10X20-304 clamp fastening set			
WPR15-30-304	150 mm	300 mm	2,30 kg



Product	H	B	G
incl.: 4x KLS 10X20-304			clamp fastening set

Stainless steel, according to ASTM 31 Ti / AISI 316 L, BS 320S17 / BS 316S11

Product	H	B	G
WPR15-10-316	150 mm	100 mm	1,64 kg
incl.: 4x KLS 10X20-316			clamp fastening set
WPR15-20-316	150 mm	200 mm	1,99 kg
incl.: 4x KLS 10X20-316			clamp fastening set
WPR15-30-316	150 mm	300 mm	2,33 kg
incl.: 4x KLS 10X20-316			clamp fastening set

H: height
B: width
G: weight

DETAILS / APPLICATIONS

