



GD

draadgoot deksel

draadgoot deksel, positieve vergrendeling

Continu thermisch verzinkt (Senzimir-techniek) (DIN EN 10346)

Product	B	L	G
GD 06S	60 mm	3000 mm	1,96 kg
GD 10S	100 mm	3000 mm	2,67 kg
GD 20S	200 mm	3000 mm	4,43 kg
GD 30S	300 mm	3000 mm	8,27 kg
GD 40S	400 mm	3000 mm	10,62 kg
GD 50S	500 mm	3000 mm	16,22 kg
GD 60S	600 mm	3000 mm	19,16 kg

Thermisch verzinkt volgens BS 729 (DIN EN ISO 1461)

Product	B	L	G
GD 06F	60 mm	3000 mm	2,05 kg
GD 10F	100 mm	3000 mm	2,73 kg
GD 20F	200 mm	3000 mm	4,64 kg
GD 30F	300 mm	3000 mm	8,69 kg
GD 40F	400 mm	3000 mm	11,21 kg
GD 50F	500 mm	3000 mm	17,14 kg
GD 60F	600 mm	3000 mm	20,28 kg



Roestvrij staal, volgens ASTM 304 / BS 304 S 3

Product	B	L	G
GD 06E	60 mm	3000 mm	2,11 kg
GD 10E	100 mm	3000 mm	2,86 kg
GD 20E	200 mm	3000 mm	4,76 kg
GD 30E	300 mm	3000 mm	8,32 kg
GD 40E	400 mm	3000 mm	10,69 kg
GD 50E	500 mm	3000 mm	16,32 kg
GD 60E	600 mm	3000 mm	19,29 kg

B: breedte
L: lengte
G: gewicht

DETAILS / TOEPASSINGEN

