



SRS-W

bevestigingsbeugel dubbel

Thermisch verzinkt volgens BS 729 (DIN EN ISO 1461)

Product	D	t	G
SRS-W 60F	60 mm	4,00 mm	0,31 kg

Roestvrij staal, volgens ASTM 304 / BS 304 S 3

Product	D	t	G
SRS-W 60E	60 mm	4,00 mm	0,31 kg

Thermisch verzinkt volgens BS 729 (DIN EN ISO 1461)

Product	D	t	G
SRS-W 30-HDG	31 mm	4,00 mm	0,21 kg
SRS-W 60-HDG	61 mm	4,00 mm	0,31 kg

Roestvrij staal, volgens ASTM 304 / BS 304 S 3

Product	D	t	G
SRS-W 30-304	31 mm	4,00 mm	0,21 kg
SRS-W 60-304	61 mm	4,00 mm	0,31 kg



Roestvrij staal volgens ASTM 31 Ti / AISI 316 L, BS 320S17 / BS 316S11

Product	D	t	G
SRS-W 30-316	31 mm	4,00 mm	0,21 kg
SRS-W 60-316	61 mm	4,00 mm	0,31 kg

D: diameter

t: materiaaldikte

G: gewicht

DETAILS / TOEPASSINGEN

