



## US 125

sluitring DIN EN ISO 7089

### Verzinkt volgens DIN EN ISO 19598 / DIN EN ISO 2081

Product	D	Ø	t	G
US 8X17	16 mm	8,4 mm	2,00 mm	0,2 kg/100
US 10X21	20 mm	10,5 mm	2,00 mm	0,4 kg/100

### Roestvrij staal, volgens ASTM 304 / BS 304 S 3

Product	D	Ø	t	G
US 8X17E	16 mm	8,4 mm	1,60 mm	0,2 kg/100
US 10X21E	20 mm	10,5 mm	2,00 mm	0,4 kg/100

### Roestvrij staal volgens ASTM 31 Ti / AISI 316 L, BS 320S17 / BS 316S11

Product	D	Ø	t	G
US 8X17E4	17 mm	8,4 mm	1,60 mm	0,2 kg/100
US 10X21E4	21 mm	10,5 mm	2,00 mm	0,2 kg/100

### Thermisch verzinkt volgens BS 729 (DIN EN ISO 1461)



Product	D	Ø	t	G
US 13X24-HDG	24 mm	13 mm	2,50 mm	0,6 kg/100

## Roestvrij staal, volgens ASTM 304 / BS 304 S 3

Product	D	Ø	t	G
US 8X17-304	16 mm	8,4 mm	2,00 mm	0,10 kg/100
US 10X21-304	20 mm	10,5 mm	2,00 mm	0,30 kg/100

## Roestvrij staal volgens ASTM 31 Ti / AISI 316 L, BS 320S17 / BS 316S11

Product	D	Ø	t	G
US 8X17-316	16 mm	8,4 mm	2,00 mm	0,10 kg/100
US 10X21-316	20 mm	10,5 mm	2,00 mm	0,20 kg/100

**D:** diameter  
**Ø:** diameter  
**t:** materiaaldikte  
**G:** gewicht

## DETAILS / TOEPASSINGEN



